

Part number:

63209-0101

Copyright

© 2012, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

August 15, 2012, 04:59 AM

Corporate Headquarters

FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
USA
Telephone: +1-503-498-3547

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Legal disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply.

Information and equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited.



General description

The FLIR A35 camera has features and functions that make it the natural choice for anyone who uses PC software to solve problems and for whom 320 x 256 pixel resolution is sufficient. Among its main features are GigE Vision and GenICam compliance, which makes it plug-and-play when used with software packages such as IMAQ Vision and Halcon.

Key features:

- Very affordable
- Compact (40 x 43 x 106 mm)
- GigE Vision and GenICam compliant
- GigE Vision lockable connector
- PoE (power over Ethernet)
- 8- and 14-bit 320 x 256 images streamed at 60 Hz, signal linear
- High frame rates (60 Hz)
- Synchronization between cameras possible
- 1x+1x GPIO
- Compliant with any software that supports GenICam, including National Instruments IMAQ Vision, Stemmers Common Vision Blox, and COGNEX Vision Pro

Typical applications:

- Automation, thermal machine vision
- Entry level "high speed" R&D

Imaging and optical data

IR resolution	320 x 256 pixels
Thermal sensitivity/NETD	< 0.05°C @ +30°C (+86°F) / 50 mK
Field of view (FOV)	48° x 39°
Focal length	9 mm (0.35 in.)
Spatial resolution (IFOV)	2.78 mrad
F-number	1.25
Image frequency	60 Hz
Focus	Fixed

Detector data

Detector type	Focal Plane Array (FPA), Uncooled VOX microbolometer
Spectral range	7.5–13 µm
Detector pitch	25 µm
Detector time constant	Typical 12 ms

Measurement

Object temperature range	–40 to +160°C (–40 to 320°F) –40 to +550°C (–40 to +1022°F)
--------------------------	--

Ethernet

Ethernet	Control and image
Ethernet, type	Gigabit Ethernet
Ethernet, standard	IEEE 802.3
Ethernet, connector type	RJ-45
Ethernet, communication	GigE Vision ver. 1.2 Client API GenICam compliant



FLIR A35 f=9 mm

P/N: 63209-0101

© 2012, FLIR Systems, Inc.
All rights reserved worldwide.

Ethernet

Ethernet, image streaming	8-bit monochrome @ 60 Hz - Signal linear/ DDE - Automatic/ Manual - Flip H&V 14-bit 320 x 256 pixels @ 60 Hz - Signal linear/ DDE GigE Vision and GenICam compatible
Ethernet, power	Power over Ethernet, PoE IEEE 802.3af class 0 Power
Ethernet, protocols	TCP, UDP, ICMP, IGMP, DHCP, GigEVision

Digital input/output

Digital input, purpose	General purpose
Digital input	1x opto-isolated, "0" < 2, "1"=2–40 VDC
Digital output, purpose	General purpose Output to ext. device (programmatically set)
Digital output	1x opto-isolated, 2–40 VDC, max 185 mA
Digital I/O, isolation voltage	500 VRMS
Digital I/O, supply voltage	2–40 VDC, max 200 mA
Digital I/O, connector type	12-pole M12 connector (shared with Digital Synchronization and External power)

Power system

External power operation	12/24 VDC, < 2.5 W absolute max
External power, connector type	12-pole M12 connector (shared with Digital I/O and Digital Synchronization)
Voltage	Allowed range 10–30 VDC

Environmental data

Operating temperature range	–15°C to +50°C (+5°F to +122°F)
Storage temperature range	–40°C to +70°C (–40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F)
EMC	- EN 61000-6-2 (Immunity) - EN 61000-6-3 (Emission) - FCC 47 CFR Part 15 Class B (Emission)
Encapsulation	IP 40 (IEC 60529)
Bump	25 g (IEC 60068-2-29)
Vibration	2 g (IEC 60068-2-6)

Physical data

Weight	0.200 kg (0.44 lb.)
Camera size (L x W x H)	106 x 40 x 43 mm (4.2 x 1.6 x 1.7 in.)
Tripod mounting	UNC ¼"-20 (on three sides)
Base mounting	4 x M3 thread mounting holes (bottom)
Housing material	Magnesium and aluminum

Shipping information

- Cardboard box
- Infrared camera with lens
- Downloads brochure
- Focus adjustment tool
- Printed Getting Started Guide
- Printed Important Information Guide
- Service & training brochure
- User documentation CD-ROM
- Registration card

Optional Accessories

- T198349 Base support
- T198348 Cable kit Mains (UK,EU,US)
- T127605 Cable M12 Pigtail



FLIR A35 f=9 mm

P/N: 63209-0101

© 2012, FLIR Systems, Inc.
All rights reserved worldwide.

Optional Accessories

- T127606 Cable M12 Sync
- T198342 Focus adjustment tool
- T911112 PoE injector

Optional Software

- T197965 FLIR Tools
 - T127648 FLIR Tools+ (license only)
 - DSW-10000 FLIR IR Camera Player
-

P/N: 63209-0101

© 2012, FLIR Systems, Inc.
All rights reserved worldwide.

T198349; Base support



General description

Adapter for connecting a tripod.

Technical data

Size (L × W × H)	55 × 34 × 9 mm (2.2 × 1.3 × 0.4 in.)
Color	Black

Shipping information

- Base support
- Four screws (plus six extra)

v1.0

T198348; Cable kit Mains (UK,EU,US)



General description

Cable kit consisting of three power cables (UK,EU,US).

Technical data

Cable length	1.5 m (4.9 ft.)
Color	Black

Shipping information

- Power cable, UK
- Power cable, EU
- Power cable, US

v1.0

P/N: 63209-0101

© 2012, FLIR Systems, Inc.
All rights reserved worldwide.

T127605; Cable M12 Pigtail



General description

Cable to access signals in M12 connector, pigtail.

Technical data

Cable length	3 m (9.8 ft.)
Connector	M12 to pigtail
Color	Black

Shipping information

- Cable

v1.0

T127606; Cable M12 Sync



General description

Cable to synchronize two cameras, M12 connectors in both ends.

Technical data

Cable length	2 m (6.6 ft.)
Connector	M12 to M12
Color	Black

Shipping information

- Cable

v1.0

P/N: 63209-0101

© 2012, FLIR Systems, Inc.
All rights reserved worldwide.

T198342; Focus adjustment tool



General description

Focus adjustment tool

Technical data

Size (L x D)	12 x 38 mm (0.47 x 1.50 in.)
Color	Blue

Shipping information

- Focus adjustment tool

v1.0

T91112; PoE injector



General description

Power supply, power over Ethernet (PoE) injector.

Technical data

AC operation	Input: 100–240 V, 50–60 Hz
DC operation	Output: 48 VDC
Power	15.4 W
Size (L x W x H)	145 x 61 x 40 mm (5.7 x 2.4 x 1.6 in.)
Color	Black

Shipping information

- Power over Ethernet (PoE) injector

v1.0

P/N: 63209-0101

© 2012, FLIR Systems, Inc.
All rights reserved worldwide.

T197965; FLIR Tools



General description

FLIR Tools is a software suite specifically designed to provide an easy way to update your camera and create inspection reports.

Key features:

- Report templates (horizontal IR + DC, vertical IR + DC, horizontal IR + IR).
- Import images from your camera to your computer.
- Apply filters when searching for images.
- Search in all texts in images and text annotations.
- Store the five latest search criterias.
- Lay out, move, and resize measurement tools on any infrared image.
- Create PDF imagesheets of any images of your choice.
- Add headers, footers, and logos to the imagesheets.
- Create PDF reports of any images of your choice.
- Add headers, footers, and logotypes to the report.
- Report editor (report page preview and snap to grid).
- Sort function (by date, groups sorted by by path and groups sorted by date)
- Browse and purchase infrared cameras, software, and accessories in our webshop.
- Software localized to 21 languages.
- Camera update (applies to FLIR Exx, T4xx and T6xx series only).

Download

This software is a freeware. To download, click the following link:

<http://support.flir.com/SwDownload/app/RssSWDownload.aspx?ID=120>

Release notes

Version	FLIR Tools 2.2
New features	• --- News in 2.2: --- • Support for rotating DC images • Improved camera connection • Various bug fixes • --- News in 2.1: --- • New text comment template tab (Create, edit and transfer templates to and from any FLIR camera. Import and export templates.). • Support for MSX (Multi-Spectral Dynamic Imaging) images. • Support for sketch images in both IR and visual with on/off toggling. • Support for same FOV ("Field of View Match"). • Display of compass information in edit and report mode. • Display of GPS information in edit and in report mode (Direct link to Google Maps for GPS-tagged images from the report). • Support for FLIR A3x5 and A6x5. • Camera tab (Logging feature. Colorized status of camera availability). • An updated toolbar in the edit window. • Support for FLIR T4xx camera models when updating the camera. • Various bug fixes.

P/N: 63209-0101

© 2012, FLIR Systems, Inc.
All rights reserved worldwide.

Shipping information

- Digital download, or
- CD-ROM

System requirements

Operating system

- Windows XP, 32-bit
- Windows Vista, 32-bit
- Windows 7, 32-bit
- Windows 7, 64-bit

v1.10

T127648; FLIR Tools+ (license only)



General description

Compared to FLIR Tools, FLIR Tools+ has the following features:

- Radiometric sequence recording
- Playback of recordings

FLIR Tools/Tools+ is a software suite specifically designed to provide an easy way to update your camera and create inspection reports.

FLIR Tools main features:

- Report templates (horizontal IR + DC, vertical IR + DC, horizontal IR + IR).
- Import images from your camera to your computer.
- Apply filters when searching for images.
- Search in all texts in images and text annotations.
- Store the five latest search criterias.
- Lay out, move, and resize measurement tools on any infrared image.
- Create PDF imagesheets of any images of your choice.
- Add headers, footers, and logos to the imagesheets.
- Create PDF reports of any images of your choice.
- Add headers, footers, and logotypes to the report.
- Report editor (report page preview and snap to grid).
- Sort function (by date, groups sorted by by path and groups sorted by date)
- Browse and purchase infrared cameras, software, and accessories in our webshop.
- Software localized to 21 languages.
- Camera update (applies to FLIR Exx, T4xx and T6xx series only).

Download

Download your copy of FLIR Tools+ here:

<http://support.flir.com/toolsplus>

Release notes

Version

FLIR Tools+ 2.2

P/N: 63209-0101

© 2012, FLIR Systems, Inc.
All rights reserved worldwide.

Release notes

New features

- --- News in 2.2: ---
- Radiometric sequence recording
- Playback of recordings
- --- News in 2.1: ---
- New text comment template tab (Create, edit and transfer templates to and from any FLIR camera. Import and export templates.).
- Support for MSX (Multi-Spectral Dynamic Imaging) images.
- Support for sketch images in both IR and visual with on/off toggling.
- Support for same FOV ("Field of View Match").
- Display of compass information in edit and report mode.
- Display of GPS information in edit and in report mode (Direct link to Google Maps for GPS-tagged images from the report).
- Support for FLIR A3x5 and A6x5.
- Camera tab (Logging feature. Colorized status of camera availability).
- An updated toolbar in the edit window.
- Support for FLIR T4xx camera models when updating the camera.
- Various bug fixes.

Shipping information

- FLIR Tools+ scratch card


System requirements

Operating system

- Windows XP, 32-bit
- Windows Vista, 32-bit
- Windows 7, 32-bit
- Windows 7, 64-bit

v1.03

DSW-10000; FLIR IR Camera Player



General description

FLIR IR Camera Player is a PC-based remote control and viewer that you can use with cameras from FLIR Systems.

You can perform one or more of the following with FLIR IR Camera Player:

- Record a video stream from the camera.
- Save a frame from the video stream as a snapshot image (*.bmp).
- Autofocus, focus far, and focus near.
- Autoadjust the camera image.
- Freeze the camera image.
- Save a camera image in the camera.
- Change Color palette.
- Add an image description and a text comment to an image.

You connect a camera in one of the following ways:

- Ethernet
- FireWire
- USB

Download

This software is a freeware. To download, click the following link:

<http://support.flir.com/SwDownload/app/RssSWDownload.aspx?ID=89>

Release notes

Version

2.2.7



Optional Software

P/N: 63209-0101

© 2012, FLIR Systems, Inc.
All rights reserved worldwide.

Release notes

New features

- --- News in 2.2.7
- Added support for FLIR Ax5 series.
- --- News in 2.2.6
- Various bug fixes.

System requirements

Operating system

- Windows XP, 32-bit
- Windows Vista, 32-bit/64-bit
- Windows 7, 32-bit/64-bit

v1.03